



SYMBOL	MILLIMETER		
	MIN.	NOM.	MAX.
A	2.200	2.300	2.400
A1	1.700	1.800	1.900
b	0.600	0.700	0.800
b1	9.700	9.800	9.900
b2	0.650	0.750	0.850
b3	1.100	1.200	1.300
c	0.400	0.500	0.600
D	10.300	10.400	10.500
D1	11.000	11.100	11.200
D2	3.200	3.300	3.400
D4	4.470	4.570	4.670
E	9.800	9.900	10.000
E1	8.000	8.100	8.200
E2	0.500	0.600	0.700
e	1.200 BSC		
e1	1.225 BSC		
H	11.600	11.700	11.800
H1	6.950 BSC		
H2	5.900 BSC		
i	0.100 REF.		
j	0.350 REF.		
K	3.100 REF.		
L	1.550	1.650	1.750
L1	0.600	0.700	0.800
L2	0.500	0.600	0.700
L3	0.400	0.500	0.600
L4	0.400	0.500	0.600
Q	6.750 REF.		
R	3.000	3.100	3.200
θ	10° REF.		



佛山市信展通电子有限公司

FOSHAN XINZHANTONG ELECTRONICS CO., LTD.

名称	TOLL-K(开尔文) 封装产品图		图号		版次	
			MD-POD-021	A		
制图	HMM	2024.07.22	单位	mm	比例	无
审核			页数: 第1页, 共1张			
批准			生效日期:			